



FT25F

Yamaha's High Thrust series of four stroke engines have been designed to deliver the grunt needed to push big loads with ease.

The FT25F is based on the standard F25 with one big difference; a higher gear ratio allows this motor to spin a larger propeller minimising slippage and getting more power to the water when you need it most.

- Perfect for yachts or pontoon boats.
- Power tilt model available.

The FT25F comes standard with Yamaha's patented dual thrust propeller that allows exhaust to escape in the opposite direction when in reverse. This gives the propeller access to undisturbed water in both directions for better traction and effortless maneuverability.

SPECIFICATIONS

| | |
|----------------------------|--------------------------|
| Engine Type | 4-Stroke, SOHC In-line 2 |
| Displacement | 498 cc |
| Bore x Stroke | 65 x 75 mm |
| Recommended Max RPM | 5500-6000 |



FT25F

| | |
|-------------------------------|------------------------------------|
| Lubrication System | Wet-sump |
| Fuel Management | Carb |
| Ignition | CDI |
| Starter System | Electric |
| Lighting Coil | 80W (MH) |
| Alternator Output | 12V – 13A with rectifier regulator |
| Operation Method | Remote control |
| Trim & Tilt Method | Power trim & tilt |



FT25F

| | |
|-----------------------------|----------|
| Fuel Tank Capacity | 24 L |
| Gear Ratio | 2.42 : 1 |
| OEDA Emission Rating | ★★★★☆ |

DIMENSIONS

| | |
|---------------|---|
| Height | <ul style="list-style-type: none">• FT25FETL : 536 mm (21.1 in)• FT25FETX : 650 mm (25.6 in) |
| Weight | <ul style="list-style-type: none">• FT25FETL : 92 kg• FT25FETX : 94 kg |